



# ISUZU CITIPORT 12

---

Manufactured by Anadolu Isuzu  
The one and only "Isuzu Manufacturing Management (IMM)" certified Isuzu factory in Europe.

# ISUZU CITIPORT 12

## TECHNICAL SPECIFICATIONS

### Dimensions (mm)

Maximum Length	12030
Maximum Width	2550
Maximum Height	3136 (w A/C)
Wheelbase	5850
Front Overhang	2700
Rear Overhang	3480

### Weights (kg)

Gross Vehicle Weight	18700
----------------------	-------

### Engine

Model	CUMMINS B6.7E6D300B
Type	Diesel EGR Turbocharged
Number of Cylinders	6
Displacement (cc)	6700
Maximum Power (kw(HP)/dd)	224 ( 300) / 2100
Maximum Torque (Nm/rpm)	1200 / 1100 – 1600
Emission Standard	Euro VI OBD-D

### Transmission

Model	AT: ZF ECOLIFE 6 AP 1200B
Number of Gears	6 Forward, 1 Reverse; Overdrive

### Steering System

Hydraulic and Adjustable Dashboard and Steering  
Wheel Column in Height and Inclination

### Tyres

Tyre Sizes	275/70 R22,5
------------	--------------

### Suspension

Front	Independent Air Suspension - 2 Bellows Electronically Controlled (ECAS)
Rear	Air Suspension - 4 Bellows Electronically Controlled (ECAS)
Anti Roll Bar	S
Kneeling System (ECAS)	S

### Brake System

Front / Rear System	Disc / Disc Full Air Brake System With EBS (Automatic Oil, Water Separator System Is Optional) Air Actuated Acted on Rear Axle
Parking Brake	Intarder (Retarder is Integrated to Transmission)
Auxiliary Brake	

### Fuel Tank


Fuel Tank Capacity (lt)	300
Adblue Tank (lt)	43

### Electrical System

Battery	24V - 2 x 240 Ah
---------	------------------

### Passenger Capacity\*

Maximum Passenger Capacity	107 Passengers
Standard Layout	27 Seated (3 foldable seats) + 83 Standing
Standard Layout with Wheelchair	24 Seated + 1(wch) + 74 Standing



## EQUIPMENTS

### Heating and Ventilation

Pre Heater	S
Fan Heater (Front/Middle/Rear)	S

### Air Conditioner

Digital Air Conditioner	S
A/C Dashboard Nozzle Diffuser for Driver	S
A/C With Heater	Opt

### Safety & Driving Comfort

Speed Limitor	S
Tachograph (Smart)	S
ABS	S
ASR	S
EBS	S
Bus Stop Brake (BSB)	S
Retarder	S
Parking Sensor	S
Spare Wheel	S
Roof Hatch for Ventilation & Emergency Exit	S (2 Units With Electrical Control)
Reverse Gear Warning Beeper	S
Fire Extinguisher	S
Engine Compartment Fire Detection System	S
Engine Compartment Fire Detection and Automatic Fire Suppression System	Opt
Fog Lamps	S (Front and Rear)
Day Time Running Lamps (DRL)	S
Rear View Camera	S
Front View Camera	S
Interior Camera	S

### Exterior

Metallic Paint	Opt
Towing Device	S

### Doors

Number of Service Doors	3 Doors
Type of Service Doors	Double Wing Air Actuated Interior Movement For All Front, Middle And Rear Doors S (with Kneeling System and Sensor) S (Front Service Door)
Wheelchair / Strollers Ramp	
Remote Control	

### Windows

Passenger Windows	Non-sliding, 1/4 Hinged Passenger Windows, Single Glazed (S) With slider, Double Glazed (Opt) Double Glazed (S) Electrically Controlled, Single Glazed with Heater (S) Windshield Blind (S), Driver Curtain (S)
Front Door Window	
Driver's Window	
Blind	

### Interior

#### Driver Seat

Driver's Seat	Air Actuated, Adjustable
Electrically Controlled and Heated Side Mirrors	S
Close-Proximity Exterior Mirror	S
Driver's Cabin	Semi Glass (S), Full Glass (Opt)
Ticket Validator Preparation	Opt
USB Charger for Driver	S

#### Passenger Compartment

Backrest (For Standing Passengers)	S
USB Charger for Passangers	Opt

### Lightening & Signalization

Interior Ceiling Lighting	S (Continuous Type With LED)
Digital Destination Display	Slither Route Display (S), Rear Route Indicator Panel (S), Colored Front Route Indicator Panel (Opt)

### Audio & Visual

Radio & MP3	S
DVD	S
Monitor / LCD Screen (Passenger Compartment)	S
Digital Clock	S

S: Standard Opt: Optional

\* Different seating variations are available.