

7" ANGLE GRINDER, WITH AFT® AND BRAKE



NEW TOOL OVERVIEW GA7070X1



FEATURES

- Anti-restart protection is engineered to prevent motor start up in the on-power switch position after a power disruption
- Soft start suppresses start-up reaction for smooth start-ups and longer gear life
- Status light indicates live power, electrical failure or worn carbon brushes
- Rotatable rear handle along with a three position side handle combine to provide increased comfort in various applications
- Power trigger comes equipped with lock-on feature for continuous operation and lock-off feature which requires two actions for power on
- Vibration absorbing rear and side handles are designed to effectively reduce vibration to the operator
- Spiral bevel gears for smoother rotations and a more efficient transfer of energy
- Labyrinth construction seals and protects the motor and bearings from dust and debris for longer tool life
- Aluminum gear housing provides superior gear alignment and smoother transmission for increased durability
- Externally accessible brushes for increased serviceability when required
- Large spindle lock for operator convenience

SPECIFICATIONS

Wheel Diameter	7"
AMPS	15
No Load Speed	8,500 RPM
Spindle Type	5/8" - 11 UNC
Lock-On Switch	Yes
Lock-Off Switch	Yes
Switch Type	Rear trigger handle
Bind-Up Control	Yes
Variable speed dial	No
Overall Length	20"
Net Weight	13.4 lbs.
Shipping Weight	16.87 lbs.
UPC Code	088381-746366

STANDARD EQUIPMENT

- 7" Angle Grinder, with AFT® (GA7070)
- 7" Wheel Guard (122939-8)
- Vibration Absorbing Side Handle (162264-5)
- Lock Nut Wrench (782412-6)

PRODUCT HIGHLIGHTS



POWER

Powerful 15.0 AMP motor delivers 8,500 RPM for optimum performance



CONVENIENCE

AFT® turns the motor off if rotation of the wheel is suddenly forced to stop



COMFORT

Rotatable rear handle along with a three position side handle provide comfort



PRODUCTIVITY

Brake stops the wheel in 3 seconds or less for maximum productivity

RELATED PRODUCTS

1. 9" Angle Grinder, with AFT® and Brake (GA9070X1)
2. 7" Cut-Off Wheel Guard (122914-4)
3. 9" Dust Extraction Cutting Guard (198509-5)
4. 7" Dust Extraction Surface Grinding Shroud (195386-6)
5. Loop Handle (199176-9)

