

## **Key Features**

- Fuel efficient, turbocharged 3 cyl. engine
- Straightforward 8 x 2 mechanical transmission
- Efficient oil-immersed, multi-disc brakes
- Hydrostatic steering for ease of operation
- Frame and sun canopy
- Front weights
- Drawbar
- Trailer tipping pipe

## **MF Dealer Support**

Exclusively available from your accredited MF Dealer:

- 12 month manufacturer's warranty
- Genuine AGCO parts
- Professional aftersales service
- Factory-approved technicians



## Specifications

	MF 360 Xtra	
Engine Performance		
Engine hp power - * Certified to BS AU 141a : (1971)	@ 2250rpm	60 hp
Max torque	@ 1350rpm	212 Nm
PTO power at rated engine speed		48 hp**
Engine		
Engine type/no. of Cylinders/Capacity/Aspiration		Diesel / T 3.1524 / 3 / Turbo / Injection
Throttle control		Hand and foot
Exhaust		Vertical
Clutch		Dual
Transmission		
Туре		Sliding Spur 8 forward, 2 reverse road speed 30 kph at 2250 engine rpm with 14.9/13-28 rear tyres
Power Take-off		
Live single speed - 540 rpm		1,789 rpm
Shaft diameter/Number of splines	r	35mm / 6
Hydraulics		
Functions		Draft control, Position control.  Response control, Constant pumping
Oil flow	litres/min	16
System pressure	Мра	21
Lift capacity at lower link ends	kg	2,145
3-point linkage		Cat 1 & 2 interchangeable balls
Brakes		
Brake type		Oil-immersed, multi-disc
Actuation		Mechanical
Parking brake		Hand lever operated
Differential lock		Mechanical
Tyres		
Front		7.50 - 16 (6PR) Pressed wheels
Rear		14.9 / 13 - 28 (6PR) Pressed wheels
Instrumentation		
Gauges	Tachometer, hourmeter, fuel level, battery condition & water temperature	
Warning lights	Direction indicators, battery charge, headlight main beam, low engine oil pressure, brake lights & auxiliary socket	

		MF 360 Xtra
Weights and Dimensions*		(with 7.50-16 front & 14.9/13-28 rear wheels
Gross weight	kg	2,335 ***
Wheelbase	mm	2,032
Overall length - (links horizontal)	mm	3,566
Overall width (min)	mm	1,930
Overall height over exhaust	mm	2,261
Overall height over steering wheel	mm	1,461
Capacities		
Fuel tank	litres	47.5
Engine sump	litres	6.8
Cooling system	litres	11.7
Hydraulic system	litres	36
Steering box	litres	2.0
Oil bath air-cleaner	litres	0.5
Turning circle		
With brakes	mm	5,867
Without brakes	mm	6,833
Ground clearance		
Under gearbox	mm	400
Front axle		
Туре		Box section, adjustable
Rear axle		
Туре		Normal-duty with epicyclic reduction
Track Adjustment		
Front	mm	1,275 - 1,884
Rear	mm	1,438 - 2,125
Steering		
Туре		Hydrostatic

## Standard equipment

Frame and sun canopy, Flat top fenders, Stabiliser chains, Weight frame with front weights (6 x 25kg), Standard tool box, Adjustable top link, Top link end Cat I & II balls, Spring suspension seat, Operator manual, Swinging drawbar & Trailer tipping pipe.



For even greater productivity a range of optional equipment is available, For full details please consult your local Massey Ferguson dealer.

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

<sup>\*</sup> Approximately \*\* Manufacturer's estimate \*\*\* Gross weight includes front weights, frame, sun canopy and swinging drawbar.